

## VELP Scientifica Digestion Units



**DK 6**



**DK 6/48**



**DK 8**



**DK 20**



**DK 20/26**



**DK 42/26**

Number of positions	6 x 250 ml	6 x 300 ml	8 x 250 ml	20 x 250 ml	20 x 100 ml	42 x 100 ml
Temperature range	Ambient to 450 °C	Ambient to 450 °C	Ambient to 450 °C	Ambient to 450 °C	Ambient to 450 °C	Ambient to 450 °C
Stability and precision of heating block temperature	± 0.5 °C	± 0.5 °C	± 0.5 °C	± 0.5 °C	± 0.5 °C	± 0.5 °C
Program library	20 user-programmable	20 user-programmable	20 user-programmable	20 user-programmable	20 user-programmable	20 user-programmable
Selectable ramps	up to 4 per program	up to 4 per program	up to 4 per program	up to 4 per program	up to 4 per program	up to 4 per program
Digestion time range	from 1 to 999 minutes	from 1 to 999 minutes	from 1 to 999 minutes	from 1 to 999 minutes	from 1 to 999 minutes	from 1 to 999 minutes
Dimensions (WxHxD) mm	293x152x339	293x152x339	233x152x448	328x138x510	293x152x339	328x138x510
	(in) (11.5x6.0x13.3)	(11.5x6.0x13.3)	(9.0x6.0x17.6)	(12.9x5.4x20.1)	(11.5x6.0x13.3)	(12.9x5.4x20.1)
Weight	Kg 16.2	15.6	21.9	20.0	18.9	17.4
	(lb) (35.7)	(34.4)	(48.3)	(44.1)	(41.4)	(37.5)
Power Supply	115 or 230 V	115 or 230 V	115 or 230 V	230 V	115 or 230 V	230 V
Power	1100 W	1100 W	1350 W	2300 W	1100 W	2300 W



[www.velp.com](http://www.velp.com)